

PRODUCT OF SINGAPORE



# MODEL 9

## 9FT MID-SIZE HVLS FAN



### 9FT FAN DIAMETER

Perfect for 4m to 8m ceiling heights



### MINIMALIST DESIGN

Sleek and slim. Blends well into any space



### ULTRA-EFFICIENT BRUSHLESS DC MOTOR

High energy efficiency with small motor size



### LOW POWER CONSUMPTION

Cost <US\$1 to run for 24 hours at max speed



### THIN-AEROFOIL BLADES

Low drag, ultra-efficient aerofoils



### QUIET OPERATION

<60dB(A). Quieter than most ambient environments



### SLANTED CEILING COMPATIBILITY

Up to 45° sloping ceiling



### AUTOMOTIVE GRADE PAINTWORK

Vibrant, long lasting colours



### SUMMER AND WINTER MODES

Forward & reverse modes to circulate and destratify



### LIGHTWEIGHT AND EASY TO INSTALL

25kg for full assembly



### ROBUST CONSTRUCTION

Aluminium and steel construction

## WHAT IS A HIGH VOLUME LOW SPEED (HVLS) FAN?

HVLS fans are large enough to produce high volumes of air while rotating at low rotational speeds.

## WHY THE MODEL 9 HVLS CEILING FAN?

Model 9 is the perfect ceiling fan for any commercial space. It is sleek and slim, incorporating a combination of advanced motor technologies and minimalist design.

## SUBSTANTIAL ENERGY SAVINGS

Model 9 performs even better in an air-conditioned environment, allowing for substantial cost savings for your energy bill.

## WHERE THE MODEL 9 HVLS FAN CAN BE USED



OFFICE  
SPACES



PLACES OF  
WORSHIP



SHOPPING  
MALLS



SPORTING  
FACILITIES



SCHOOLS



LIBRARIES




SHOWROOMS

## TECHNICAL SPECIFICATIONS


Fan diameter	2.77m (109 inches or 9.09ft)
Blades	6 aluminium thin aerofoil blades
Ceiling to fan base (standard option)	1.18m (46.5inches)
Complete fan weight	25kg
Ideal floor to ceiling height	4m to 8m
Motor technology	Brushless DC with rare earth neodymium permanent magnets
Speed control	5 speeds with reverse (winter) option
Fan control	RF wireless remote (single remote, multi-fans control possible)
Wall control	Available as option
Estimated airflow	>15,000cfm at max speed
Power source (input)	230/240VAC, 50/60Hz, 1Ph, 13A
Fan power consumption	120W, 104RPM on max speed
Sound level at max speed	<60dB(A)
Safety	Safety cable to Independent Anchor Point
Standard colours	Matt Black and Gloss White
Certifications	CE Mark, IECEE CB



### Air Diffusion Agencies

 101 Frederick Street, Wellend, SA 5007  
 [bill@airdiffusion.com.au](mailto:bill@airdiffusion.com.au)

 [www.airdiffusion.com.au](http://www.airdiffusion.com.au)

 (08) 8116 3600 (ph)  
(08) 8116 3605 (fax)

Showrooms



Warehouses



Office spaces

