

SIMPLE TO USE

No installation required! It's easy! Plug the unit into a standard electrical wall outlet and connect to a water supply with a fixed hose connection. If a water outlet is not available the CoolBreeze Mobile can be filled manually with a hose.

For maximum efficiency, place the air conditioner in an open doorway or in front of an open window to ensure plenty of fresh, cool air.

THE BENEFIT OF MOBILE

The Commercial Mobile has a direct drive fan coupled with a heavy duty motor which guarantees long term performance. With the equivalent capacity of an average roof mounted evaporative air conditioner, a CoolBreeze Mobile makes great sense. It's suitable for leased premises and provides all of the benefits of a fixed installation system with the flexibility to take it with you when you move.

TRANSPORT FRAME

The CoolBreeze Mobile unit is fitted with heavy duty casters to allow it to be moved easily and to provide maximum cooling where it is needed most. If the unit is transported often from site to site, the optional transport frame allows the unit to be strapped down on a ute or truck.

Wheelie Cool
PORTABLE INDUSTRIAL COOLERS

WheelieCool mobile air conditioner is ideal for Factories, Workshops, Warehouses, Outdoor Areas, Unloading Containers - any big space that needs to be cooled. Just plugs into a standard power-point and garden hose (or manually fill the large capacity water tank). No installation required.

Local Dealer:

Western Australia

- ☎ (08) 9350 2200
- ✉ sales@coolbreeze.com.au
- 📍 131 Bannister Rd
Canning Vale WA 6155

Victoria

- ☎ (03) 8336 10425
- ✉ sales@coolbreeze.com.au
- 📍 5 Hawker Street
Airport West, Victoria 3042

COOL BREEZE
air conditioning

COOL BREEZE
air conditioning



Wheelie Cool
PORTABLE INDUSTRIAL COOLERS

COMMERCIAL MOBILE
**EVAPORATIVE AIR
CONDITIONER**

MODEL M240 - MOBILE MOTOR

MOTOR	Voltage (V)	220-240
	Watts	1000W
	Amp Draw - low/high current (AMPS)	5.0/6.0
	RPM - low/high SPEED (RPM)	850/1370
	Watts - Low	680
	Watts - Medium	800
	Watts - High	1270
FAN	Powerflow Fixed Pitch	
WATER	Inlet Connection	1/2 inch BSP
	Drain (TAP)	Manual
	Tank Capacity (Litres)	100
FILTER MEDIA	Number of Pads	3
	Size (mm)	3 x 830 x 930
	Thickness (mm)	100
COOLING CAPACITY m² (Comcool Zone 2)		150-240 m ²
DESIGN AIR FLOW	Lit/sec	3000
DEPTH/WIDTH (MM)		1130 x 1220
HEIGHT (MM)		1540
SHIPPING WEIGHT (KG)		95
SHIPPING VOL (M³)		1.9
OPERATING WEIGHT (KG)		195

Cooling Capacity may vary depending on area and environmental conditions

Wheelie Cool
PORTABLE INDUSTRIAL COOLERS



FAN SPEED CONTROL

- Variable Speed touch controller.



FAN ONLY OPERATION

Switch to FAN MODE to circulate fresh outside air which is helpful to remove odours or fumes from the worksite.



FEATURES

- 100mm thick pads ensure an unrestricted even airflow
- Large capacity 100lt water tank with drain
- Easy to move with heavy duty wheels, two with brakes
- Robust powder coated steel frame
- Fully adjustable multi-directional grille
- Optional Tie-down frame available
- All polymer construction – no corrosion
- Low maintenance direct drive fan (no belts or pulleys)
- Quieter operation – special dimpled fan
- Easy to clean and service



WARRANTY

- 2 Years Labour
- 2 Years Parts
- 10 Years Casing



USES FOR WHEELIE COOL

- Agricultural
- Shearing Sheds
- Dog Kennels
- Aviation
- Automotive
- Restaurants & Cafes
- Weddings & Events
- Home Patios
- Mechanical Workshops
- Mining Workshops
- Equipment Cooling
- Temporary Cooling
- Home Shed or Man Cave
- Cooling Stations
- Industrial Cooling
- Sporting Events
- Personnel Cooling
- Poultry Cooling

